



## Performance

### Maximum Lift Capacity (on Tires)

#### Front

- 15,000 lbs. (6,804 kg)

#### Side

- 12,000 lbs. (5,443 kg)

### Maximum Lift Capacity (on Hi-rail)

#### Front

- 15,000 lbs. (6,804 kg)

#### Side

- 8,000 lbs. (3,629 kg)

### Boom Rotation

- 360° Continuous

### Maximum Travel Speed

- 25 mph (40.2 km/h)

## Standard Equipment

### Engine

- Cummins QSB 6.7
- 190 hp (141.7 kW) at 2,200 rpm
- 100 Gallon (379 L) Fuel Capacity

### Transmission

- Dana T32000
- Electric Powershift Control

### Axles

- Planetary, hypoid ring gear and pinion with planetary reduction at wheels

### Drive

- Four-wheel with rear wheel disconnect
- Hi/Lo Range

### Brakes

- Four-wheel Outboard Dry Disc Brakes
- SAHR Park Brake

### Tires

- Front and Rear 16.00 R25

### Hydraulic System

- 75 Gallon (284 L) Hydraulic Oil Reservoir Capacity with Dirt Box Filtration

- Gear Pump (Dedicated Steering Pump)

- 14 gpm (53.0 Lpm)
- 2,200 rpm

- Piston Pump (All Functions Except Steering)

- 80 gpm (302.8 Lpm)
- 2,200 rpm

### Controls

- Full IQAN® Electronically Controlled Hydraulics

### Cab

- ROPS/FOPS Cab with Tinted Safety Glass
- Front and Rear Window Wipers
- Digital Display

## Optional Equipment

- Warning Beacon
- Rail Sanders
- Train Brakes
- Turn Signals/Hazard Lights
- Passenger Seat
- Air Conditioner
- Emergency Power Unit
- Engine Block Heater
- Night Lighting Package
- Machine Fluid Heaters
- Fenders (front and rear)
- Vandal Covers
- Heavy Duty Rear Bumper
- Cab Heater
- Hydraulic top-off System
- Spare Tire Carrier
- Hi-Rails (insulated or non)
- Locks on Tanks and Tool Box



## Dimensions

### Height

- 10' 9" (3.3 m)

### Width

- 8' 8" (2.6 m)

### Length

- 26' 10" (8.2 m)

### Curb Weight<sup>A</sup> (with Hi-rail)

- 45,535 lbs. (20,654 kg)

### Curb Weight<sup>A</sup> (without Hi-rail)

- 40,535 lbs. (18,386 kg)

## Optional Attachments

- Hi-Rail
- Train Brakes
- Drawbar Coupler
- Rail Threader
- Magnet
- Switch Broom
- Auger
- Grapple
- Clamshell
- Cribbing Bucket
- V-Type Snow Plow
- Back Filler Blade
- Loader Bucket
- Track Cleaning Bucket
- Snow Bucket
- Extendible Boom
- Lattice Boom
- Tote Hooks
- Backhoe
- Brush Cutter
- Front-Mounted Winch

## Contact Information

### Pettibone

1100 Superior Avenue  
Baraga, MI 49908  
800.GO.PETTIBONE

[gopettibone.com](http://gopettibone.com)

NOTE: The Company reserves the right to change specifications and prices without notice in order to follow its policy of constantly striving to manufacture a better product without incurring any liability to provide these new features on any units previously manufactured. Prices and specifications subject to change without notice.

<sup>A</sup> Approximate